

## TNC Series 2 Watts



**Model 9042 & 9036 (Nickel Plated Brass)**  
Frequency Range..... DC to 12.4GHz  
Available Values...0-10, 12, 15, 20, 30 & 40dB

**Models 18T (Stainless Steel)**  
Frequency Range...0-10, 12, 15, 20, 30, 40, 50, 60dB  
Available Values  
Accuracy of Attenuation:  
0 through 6dB.....±0.3dB maximum  
7 through 20dB.....±0.5dB maximum  
30dB.....±0.75dB maximum  
40dB.....±1.0dB maximum  
50 & 60dB.....±1.50dB maximum\*  
VSWR:  
DC to 4GHz.....1.15:1 maximum  
4GHz to 8GHz.....1.20:1 maximum  
8GHz to 12.4GHz.....1.25:1 maximum  
12.4GHz to 18GHz.....1.35:1 maximum\*

\*18T only

Complete Specification Sheet Available

## N Series (50 and 75 Ohms)



**50 Ohms**  
**Nickel Plated Brass**  
**Models 9070 (2 Watts)**  
Frequency Range.....DC to 6GHz  
Available Values.....10, 12, 15, 20, 30, and 40 dB  
VSWR:  
DC to 2GHz.....1.25:1 maximum

**Models 2N, 6N, 18N (Stainless Steel)**  
**(2 Watts)**  
Frequency Range..... DC to 18GHz  
Available Values.....0-10, 12, 15, 20, 30, 40, 50 and 60dB  
VSWR:  
DC to 4GHz.....1.15:1 maximum  
4GHz to 8GHz.....1.20:1 maximum  
8GHz to 12.4GHz.....1.25:1 maximum  
12.4GHz to 18GHz.....1.35:1 maximum

**75 Ohms**  
**Model 4N-XX/75 (2 Watts)**  
Frequency Range.....DC to 4GHz  
Available Values.....1, 2, 3, 6, 10, 20 and 30dB  
VSWR.....1.30:1 maximum

Complete Specification Sheet Available

## BNC Series (50 and 75 Ohms)



**50 Ohms**  
**Model 9033 (2 Watts)**  
Frequency Range..... DC to 4 GHz  
Available Values..... 0-10, 12, 15, 20, 30dB  
VSWR:  
DC to 4GHz.....1.25:1 maximum

**Model 9014 (2 Watts)**  
Frequency Range .....DC to 4 GHz  
Available Values.....40, 50 & 60 dB  
VSWR:  
DC to 4 GHz.....1.25:1 maximum

**Model 2051 (2 Watts)**  
Frequency Range.....DC to 12.4 GHz  
Available Values.....3, 6, 10, 20 & 30dB  
VSWR:  
DC to 4GHz.....1.25:1 maximum  
4GHz to 8GHz.....1.30:1 maximum  
8GHz to 12.4GHz.....1.35:1 maximum

**75 Ohms**  
**Model 9033-XX/75 (2 Watts)**  
Frequency Range..... DC to 4GHz  
Available Values..... 0, 3, 6, 10, 20 & 30dB  
VSWR:  
DC to 1GHz.....1.10:1 maximum  
1GHz to 2GHz.....1.20:1 maximum  
2GHz to 4GHz.....1.35:1 maximum

Complete Specification Sheet Available


MODEL NO.    FREQ. (GHz)    CONNECTOR    VSWR    ATTN (dB)

### 0.5 Watt, 1 Watt and 2 Watt Attenuators


AS398 (1 Watt)	3	SMA-M/F	1.20:1	1-10,12,15,20,30
AHC	6	SMA-M/F	1.20:1	1-10,12,15,20,30
9026, (Style A)	18	SMA-M/F	1.60:1	0-10,12,15,20,30
9029, (Style AH)	18	SMA-M/F	1.60:1	0-10,12,15,20,30
9023, (Style B)	18	SMA-M/F	1.60:1	0-10,12,15,20,30,40,50,60
2A, 2AH	2.5	SMA-M/F, M/M, F/F	1.15:1	0-10,12,15,20,30,40
2B	2.5	SMA-M/F, M/M, F/F	1.15:1	0-10,12,15,20,30,40,50,60
2C	2.5	SMA-M/F	1.15:1	0-10,12,15,20,30
2DH	2.5	SMA-M/F, M/M, F/F	1.15:1	0-10,12,15,20,30,40
6A, 6AH	6	SMA-M/F, M/M, F/F	1.20:1	0-10,12,15,20,30,40
6B	6	SMA-M/F, M/M, F/F	1.20:1	0-10,12,15,20,30,40,50,60
6C	6	SMA-M/F	1.20:1	0-10,12,15,20,30
6DH	6	SMA-M/F, M/M, F/F	1.20:1	0-10,12,15,20,30,40
18A, 18AH	18	SMA-M/F, M/M, F/F	1.35:1	0-10,12,15,20,30,40
18B	18	SMA-M/F, M/M, F/F	1.35:1	0-10,12,15,20,30,40,50,60
18C	18	SMA-M/F	1.35:1	0-10,12,15,20,30
18DH	18	SMA-M/F, M/M, F/F	1.35:1	0-10,12,15,20,30,40
23A, 23AH	23	SMA-M/F, M/M, F/F	1.40:1	0-10,12,15,20,30,40
23DH	23	SMA-M/F, M/M, F/F	1.35:1	0-10,12,15,20,30
26A, 26AH	26.5	2.9mm-M/F	1.40:1	0,3,6,10,20,30
40A, 40AH (0.5W)	40	2.9mm-M/F	1.40:1	0,3,6,10,20,30
40A2W, 40AH2W	40	2.9mm-M/F	1.40:1	3,6,10,20,30
40EH (0.5W)	40	2.4mm-M/F	1.60:1	0,3,6,10,20,30
50EH (0.5W)	50	2.4mm-M/F	1.75:1	0,3,6,10,20,30
50V	50	1.85mm-M/F	1.75:1	3,6,10

H=with Hex


See pages 2 and 3 and above for more detailed specifications. All models 2 Watt unless indicated




AS398




SMA A Series




SMA AH Series




SMA B Series




SMA C Series




SMA DH Series



2.9mm 26A, 40A Series



2.9mm 26AH, 40AH Series



2.4mm EH Series